

????????????????? ??????????? LW26-25S 25A , 4 ????????



?????????????: ??? ?????????????? ??????

?????

?????? ????? ?? ??? 33,89 €

???? ?? ??????? 27,33 €

???? ??????? ?? ???????

???? ??????? 33,89 €

???? ??????? ????? ??? 27,33 €

????????? ?????? 6,56 €

[????????? ??? ?? ???????](#)

????????????? [Elmark](#)

??????????

**Technical characteristics:**

- Power supply voltage: 230/400V, 50Hz
- Number of levels: 4
- Number of positions: 3
- Insulation voltage: 690V
- Impulse voltage withstand: 6000V
- Mechanical wear resistance: 3?105 commutation cycles
- Operating temperature: -10°? - +50°?
- Humidity: 35 - 85%RH
- Commutation capacity: 25-160?
- Resistant to UV rays plastic
- Cable connection: screw joining
- Tightening torque of the bolt: 1.33Nm
- Maximum section of the power supply conductors: 16.0mm2

**Mounting:**

- Directly to the control panel
- Thickness of the surface: max 5mm

**Standards:** EN 60947-1; EN 60947-3-1

?????????????: ?????? ??????????: **base\_uom/descry** ??????: E1 ??????????: E174 ??????????: 3+2 Three years standard + two years extended

?????? ??????????????: IP42

????????????? ??????: 25A

?????: ELMARK

????????? ??????????: 4

????????? ??????????: 4

?????????: 3+2

M?????????: LW26

?????????: 3