


H05VV-F 2x0,75mm2



?????????: ??? ???????????? ?????
????
?????? ??? ? ? ? 0,39 €

???? ? ? ?????? 0,32 €

???? ?????? ? ? ??????

???? ?????? 0,39 €

???? ?????? ?????? ??? 0,32 €

????????? ?????? 0,08 €

[???????? ??? ?? ?????](#)

????????????[Elmark](#)

????????

Cable with parallel or stranded in a bundle insulated cores, used for connection of electrical appliances to the electrical network. Also, for connection of mobile devices and appliances.

Technical characteristics:

- Flexible cable according to HD 21.5 S3, DIN VDE 0281, part 5
- Rated voltage: U0/U - 300/300V
- Test voltage: 2000V
- Maximum conductor temperature: +70°C
- Ambient temperature: -30°C to +50°C
- Minimum bending radius during installation: 7.5xD
- D - cable height

Construction:

- Flexible Copper wires, class 5 according DIN VDE 0295, IEC 60228
- Insulation: PVC compound
- Colour coding: according DIN VDE 0293-308
- Sheath: PVC compound
- Sheath colour: white, black

?????????: ?????? ?????????: **base_uom/descry** ?????: C3 ?????????: C323 ??????: 5+2 Five years standard + two years extended

?????: ELMARK

?????: ?????????? ???????

????????? ??????: 2

?????????: 0.75 mm²

?????????: 5+2

*?????????: ???? ??? ?????